

Factory Activated, Maintenance Free 12v Battery Specifications

Battery Type	Capacity AH (10H-R)	Dimensions -Inches L/W/H	Dimensions -Millimeters L/W/H	Assembly Figure (as per cover polarity)	Weight Lbs.	Terminal Type (refer to pg 5)	Acid Volume (liter)	Regular Charge Current (amp)	CCA @ 0°F (-18°C)
GT7-B4	6.5	5 ^{7/8} /2 ^{9/16} /3 ^{5/8}	151/66/94		6	4	N/A	0.6	110
GT12-B4	10	5 ^{7/8} /2 ^{11/16} /5 ^{1/16}	151/70/131		10	4	N/A	1.0	190
GT14-B4	12	5 ^{7/8} /2 ^{3/4} /5 ^{11/16}	150/69/145		11	4	N/A	1.2	210
YGIX30	27.5	6 ^{9/16} /5/6 ^{7/8}	166/126/175		22	10	N/A	2.8	335

Maintenance Free 12v Battery Specifications

Battery Type	Capacity AH (10H-R)	Dimensions -Inches L/W/H	Dimensions -Millimeters L/W/H	Assembly Figure (as per cover polarity)	Weight Lbs.	Terminal Type (refer to pg 5)	Acid Volume (liter)	Regular Charge Current (amp)	CCA @ 0°F (-18°C)
GT4L-BS	3	4 ^{1/2} /2 ^{13/16} /3 ^{3/8}	114/71/86		2.9	5	0.18	0.4	45
GTX5L-BS	4	4 ^{1/2} /2 ^{13/16} /4 ^{3/16}	114/71/106		3.5	5	0.24	0.5	70
GTX7A-BS	6	6/3 ^{7/16} /3 ^{3/4}	150/87/94		5.3	5	0.33	0.7	100
GTX7L-BS	6	4 ^{1/2} /2 ^{13/16} /5 ^{3/16}	114/71/131		5.1	5	0.33	0.6	90
GTX9-BS	8	6/3 ^{7/16} /4 ^{3/16}	150/87/105		5.4	5	0.40	0.9	130
GTX12-BS	10	6/3 ^{7/16} /5 ^{1/8}	150/87/130		7.5	5	0.60	1.2	180
GTX14-BS	12	6/3 ^{7/16} /5 ^{3/4}	150/87/145		8.1	5	0.70	1.4	200
GT16-BS	19	6 ^{15/16} /4/6 ^{1/8}	176/101/156		10.3	4	0.78	4.7	210
GT16L-BS	19	6 ^{15/16} /4/6 ^{1/8}	176/101/156		10.3	4	0.78	4.7	210
GTX18L-BS	20	8 ^{1/8} /3 ^{9/16} /6 ^{7/16}	206/91/164		11.2	4	0.93	5.1	250
GTX20-BS ¹	18	6 ^{7/8} /3 ^{7/16} /6 ^{1/8}	175/87/155		11.2	4	0.93	1.8	270
GTX20L-BS ¹	18	6 ^{7/8} /3 ^{7/16} /6 ^{1/8}	175/87/155		11.2	4	0.93	1.8	270

¹ The GTX20 series batteries may be used as an optional upgrade, but some modification to the hold down may be necessary. See battery label for retrofit cautions.

High Performance Polimion 12v Battery Specifications

Battery Type	Capacity AH (10H-R)	Dimensions -Inches L/W/H	Dimensions -Millimeters L/W/H	Assembly Figure (as per cover polarity)	Weight Lbs.	Terminal Type (refer to pg 5)	Acid Volume (liter)	Regular Charge Current (amp)	CCA @ 0°F (-18°C)
CB2.5L-C	2.5	3 ^{3/16} /2 ^{3/4} /4 ^{1/8}	80/70/105		1.7	-	8.1	0.3	16
CB2.5L-C-1	2.5	3 ^{3/16} /2 ^{3/4} /4 ^{1/8}	80/70/105		1.7	-	8.1	0.3	16
CB3L-A	3	3 ^{7/8} /2 ^{1/4} /4 ^{3/8}	98/56/110		2.5	6	8.1	0.3	36
CB3L-B	3	3 ^{7/8} /2 ^{1/4} /4 ^{3/8}	98/56/110		2.5	6	8.1	0.3	36
CB4L-A	4	4 ^{3/4} /2 ^{3/4} /3 ^{5/8}	120/70/92		2.8	5	10.1	0.4	45
CB4L-B	4	4 ^{3/4} /2 ^{3/4} /3 ^{5/8}	120/70/92		2.8	5	10.1	0.4	45
CB5L-B	5	4 ^{3/4} /2 ^{3/8} /5 ^{1/8}	120/60/130		3.5	6	12.2	0.5	67
CB7-A	8	5 ^{5/16} /3/5 ^{1/4}	135/75/133		5.1	6	20.3	0.8	113
YB7C-A	8	5 ^{1/8} /3 ^{9/16} /4 ^{1/2}	130/90/114		5.1	3	20.3	0.8	124
CB7L-B	8	5 ^{5/16} /3/5 ^{1/4}	135/75/133		5.1	11	20.3	0.8	113
CB9A-A	9	5 ^{5/16} /3/6 ^{1/8}	135/75/155		5.3	6	20.3	0.9	125

High Performance Polymion 12V Battery Specifications (continued)

Battery Type	Capacity AH (10H-R)	Dimensions -Inches L/W/H	Dimensions -Millimeters L/W/H	Assembly Figure (as per cover polarity)	Weight Lbs.	Terminal Type (refer to pg 5)	Acid Volume (liter)	Regular Charge Current (amp)	CCA @ 0°F (-18°C)
CB9L-A2	9	5 ^{5/16} /3/5 ^{1/2}	135/75/139		5.3	4	20.3	0.9	132
CB9-B	9	5 ^{5/16} /3/5 ^{1/2}	135/75/139		5.3	6	20.3	0.9	132
CB9L-B	9	5 ^{5/16} /3/5 ^{1/2}	135/75/139		5.3	6	20.3	0.9	132
CB10A-A2	11	5 ^{5/16} /3 ^{9/16} /6 ^{1/8}	135/90/155		7.0	8	27.0	1.1	160
CB10L-A2	11	5 ^{5/16} /3 ^{9/16} /5 ^{3/4}	135/90/145		7.0	8	27.0	1.1	185
CB10L-B	11	5 ^{5/16} /3 ^{9/16} /5 ^{3/4}	135/90/145		7.0	6	27.0	1.1	185
CB10L-B2	11	5 ^{5/16} /3 ^{9/16} /5 ^{3/4}	135/90/145		7.0	8	27.0	1.1	185
CB12A-A ¹	12	5 ^{5/16} /3 ^{3/16} /6 ^{5/16}	134/80/160		6.8	6	27.0	1.2	188
CB12AL-A	12	5 ^{5/16} /3 ^{3/16} /6 ^{5/16}	134/80/160		6.8	6	25.4	1.2	188
CB12B-B2	12	6 ^{5/16} /3 ^{9/16} /5 ^{1/8}	160/90/130		7.1	8	27.0	1.2	170
CB12C-A	12	5 ^{5/16} /3 ^{3/16} /6 ^{7/8}	134/80/175		7.1	4	27.0	1.2	170
CB14-A2	14	5 ^{5/16} /3 ^{1/2} /6 ^{9/16}	134/89/166		7.6	8	30.4	1.4	200
CB14A-A	14	5 ^{5/16} /3 ^{1/2} /6 ^{15/16}	134/89/176		7.9	6	30.4	1.4	200
CB14-A2	14	5 ^{5/16} /3 ^{1/2} /6 ^{15/16}	134/89/176		7.9	8	30.4	1.4	200
CB14L-A1	14	5 ^{5/16} /3 ^{1/2} /6 ^{9/16}	134/89/166		7.6	1	30.4	1.4	200
CB14L-A2	14	5 ^{5/16} /3 ^{1/2} /6 ^{9/16}	134/89/166		7.6	8	30.4	1.4	200
CB14L-B2	14	5 ^{5/16} /3 ^{1/2} /6 ^{9/16}	134/89/166		7.6	8	30.4	1.4	200
CB14-B2	14	5 ^{5/16} /3 ^{1/2} /6 ^{9/16}	134/89/166		7.6	8	30.4	1.4	200
SCB14L-A2 ²	14	5 ^{5/16} /3 ^{1/2} /6 ^{9/16}	134/89/166		7.6	8	30.4	1.4	200
SCB14L-B2 ²	14	5 ^{5/16} /3 ^{1/2} /6 ^{9/16}	134/89/166		7.6	8	30.4	1.4	200
CB16AL-A2	16	8 ^{1/8} /2 ^{13/16} /6 ^{7/16}	207/71.5/164		8.6	2	37.2	1.6	200
HCB16A-A	16	6 ^{3/8} /7 ^{1/16}	151/91/180		8.5	7	30.4	1.6	210
CB16-B	19	6 ^{7/8} /4/6 ^{1/8}	175/100/155		10.5	6	40.6	1.9	225
CB16L-B ¹	19	6 ^{7/8} /4/6 ^{1/8}	175/100/155		10.5	6	40.6	1.9	225
CB16CL-B	19	6 ^{7/8} /4/6 ^{7/8}	175/100/175		10.1	4	40.6	1.9	225
SCB16L-B ²	19	6 ^{15/16} /4/6 ^{1/8}	175/100/155		9.3	6	43.9	1.9	225
CB18-A	18	7 ^{1/8} /3 ^{9/16} /6 ^{3/8}	180/90/162		9.4	7	40.6	1.8	245
CB18L-A	18	7 ^{1/8} /3 ^{9/16} /6 ^{3/8}	180/90/162		9.4	7	40.6	1.8	245
C50-N18L-A3 ¹	20	8 ^{1/8} /3 ^{9/16} /6 ^{3/8}	205/90/162		11.2	4	47.3	2.0	285
C60-N24L-A28		7 ^{1/4} /4 ^{7/8} /6 ^{7/8}	184/124/175		14.4	3	6.5	1.7	265
CB30L-B	30	6 ^{5/8} /5 ^{3/16} /6 ^{15/16}	168/132/176		14.1	4	57.5	3.0	300

¹ Sensor available for this battery.

² This battery includes a sensor.